

Screw Ring Gauges UNF



Screw Ring Gauges:

ISO Threads  
 6g Tolerance  
 Knurled outer surface  
 GO: Thick body  
 NO-GO Thin body +Surface hole

CODE NO.	SIZE	CLASS	TYPE	PITCH DIA.
53-854-032	4 - 48 UNF	2A	GO PD	0.0978
53-855-032	4 - 48 UNF	2A	NO GO PD	0.0954
53-854-033	1/4 - 28 UNF	2A	GO PD	0.2258
53-855-033	1/4 - 28 UNF	2A	NO GO PD	0.2225
53-854-034	5/16 - 24 UNF	2A	GO PD	0.2843
53-855-034	5/16 - 24 UNF	2A	NO GO PD	0.2806
53-854-035	3/8 - 24 UNF	2A	GO PD	0.3468
53-855-035	3/8 - 24 UNF	2A	NO GO PD	0.3430
53-854-036	7/16 - 20 UNF	2A	GO PD	0.4037
53-855-036	7/16 - 20 UNF	2A	NO GO PD	0.3995
53-854-037	1/2 - 20 UNF	2A	GO PD	0.4662
53-855-037	1/2 - 20 UNF	2A	NO GO PD	0.4619
53-854-038	9/16 - 18 UNF	2A	GO PD	0.5250
53-855-038	9/16 - 18 UNF	2A	NO GO PD	0.5205
53-854-039	5/8 - 18 UNF	2A	GO PD	0.5875
53-855-039	5/8 - 18 UNF	2A	NO GO PD	0.5828
53-854-040	3/4 - 16 UNF	2A	GO PD	0.7079
53-855-040	3/4 - 16 UNF	2A	NO GO PD	0.7029