
	<p>Chamfers the outside diameters of shafts and tubes Cranked rotating arm provides fast and effortless use</p> <p>Consists of:</p> <p>1 x NG-1Handle 1 x EX 2001 External Chamfering Head</p>
---	--

Packed Weight and Dimensions

Code	Description	Weight g	W mm	H mm	L mm
NG 1700	External Rotodrive	57	31	31	152

	<p>Instructions</p> <p>Do not use heavy pressure when deburring as this will cause the blade to dig into the material and give an uneven finish Use light and even pressure which will allow the blade and handle to work together to remove the burr and leave a smooth finish on the component</p> <p>Blades should be handled carefully as they are sharp and can cut Blades can break causing flying objects Sharp edges and flying objects can cause injury Users and bystanders should wear protective safety glasses Do not pry or bend blades Keep blades and sharp tools away from children Do not regrind blades as this will weaken the blade and cause breakage and possible injury</p> <p>All Noga products meet the strict requirements of ISO 9001 and ISO 14001</p>
---	--

NG-1 Handle

	<p>NG-1 Handle accepts all “S” type Blades Ergonomic soft grip, acetyl and rubber construction Removable end cap for blade storage 125mm long x 28mm maximum diameter Blades are secured by pulling back the front locking mechanism and are free to rotate</p>
---	---

Packed Weight and Dimensions

Code	Description	Weight g	W mm	H mm	L mm
NG-1 Handle	NG1000	45	32	32	153

External Rotodrive

EX 2001 External Rotodrive Chamfering Head

		<p>90° External Rotodrive Chamfer Head Range: 4 – 18mm diameter Blade shank diameter 3.2mm Blade material: HSS M2 Blade hardness: 62-64 HRC Used with NG-1 Handle or S Holder with NG-3 Handle</p>
--	---	--

Packed Weight and Dimensions

Code	Description	Weight g	W mm	H mm	L mm
EX 2001	External Chamfering Head 4-18mm	15	36	22	70